205 Commercial Court
Morganville, NJ 07751
Phone: (732) 591-5800 Fax: (732) 591-5801 E-mail: sales@auroramultimedia.com

V-Tune Pro HD Architectural Specifications

Minimum tuner requirements:

- Unit shall be capable of ATSC and QAM 64/256.
- Unit shall support analog NTSC.
- Unit shall have integrated 10/100 LAN for IPTV.
- Unit shall have MPEG2, MPEG4, H.264, and VC-1 decoding capabilities.
- Unit shall decode resolutions up to 1080p.
- Unit shall have front LED display with menu keypad control.
- Unit shall have IR remote control with IR extender capabilities.
- Unit shall be firmware upgradeable via USB or Internet.
- Unit shall have simultaneous low resolution and high resolution outputs.
- Unit shall have HDMI 1.3, YPbPr, S-Video, and Composite video outputs.
- Unit shall have analog stereo, S/PDIF and optical audio outputs.
- Unit shall have On Screen Display, Closed Captioning, and parental controls.
- Unit shall have RS-232 control.
- Unit shall have built in Ethernet control with the ability to serve up web control.
- Unit shall be RoHS compliant
- Units shall be rack mountable in a 1RU space and include rack ears.

The tuner shall include the following hardware configuration:

- ATSC / QAM / NTSC signal reception
- IPTV
- H.264, MPEG-2, MPEG-4, VC-1
- Video Outputs: HDMI, YPbPr, S-Video, Composite Video
- Audio Outputs: Stereo RCA, S/PDIF Coaxial and Optical
- Front LED display with front panel control
- IR Input (Remote IR receiver window)
- Closed captioning
- V-Chip support
- Automatic and manual channel scan
- RS-232 Control
- 10/100 LAN Port for IPTV, LAN control, Web Pages
- Dimensions 10.63” x 7.0” x 1.75”