

## ReAX™ IP Control Server



Introducing the all new RXS-1, the solution to your AV over IP control needs. Loaded out of the box with Aurora's own IPBaseT Pro Server control software and the new, powerful non-proprietary ReAX™ control engine. Powered by Linux, the RXS-1 All-in-One control system, comes packed with an Intel® Core i5 processor, 8GB RAM, a 128GB SSD, and a five (5) year warranty.

The RXS-1 is designed to interface with Aurora's AV over IP line of transceiver products. Seamless integration with the VLX and IPX product lines allows for easy setup and faster installations.

### Features:

- **ReAX™ Control Engine**
- **IPBaseT Manager Pro**
- **2 HDMI Outputs**
- **2 1Gbps LAN Ports**
- **4 USB 2.0**
- **4 USB 3.0**
- **Fiber Optic Audio Output**
- **Mic Input**
- **Speaker/Line Out**
- **Integrated Wi-Fi**
- **SD Card**
- **Linux OS**
- **Intel i5 Processor**
- **128GB SSD**
- **Fanless Design**

## Technical Specifications:

Model Name	RXS-1
<b>Technical</b>	
Processor	Intel® Core i5-5200U 2.2GHz Dual Core
Memory	8GB RAM
Storage	128GB SSD + SD Card Slot
Graphics	Intel® HD graphics 5500 graphics card (32-bit color depth)
HDMI	2 HDMI 4K30 4:4:4
Audio	Mic, Speaker/Line, Optical
Wi-Fi	300M Internal
USB-20	4 Type A
USB 3.0	4 Type A
LAN	2 1G RG-45
<b>Mechanical</b>	
Housing	Metal Enclosure
Dimensions [L x W x H]	22.4 x 17.7 x 4.9cm (8.81" x 6.96" x 1.92")
Weight	1.66kg (3.66 lbs.)
Mounting	Desktop Horizontal or Vertical
Power Supply	12v 5A DC
Power Consumption	60 Watts Max
Operation Temperature	0~40° C [32~104° F]
Storage Temperature	-20~60° C [-4~140 °F]
Relative Humidity	20~90% RH [No Condensation]

**Note: Specifications subject to change without notice.**

**Important: Read User Guide for full specifications.**